

INNOVATION. COMMITMENT. EXCELLENCE



## **Features**

Compatible with ESC/POS and Star commands

Waterproof, oil-proof, dust-proof structure

Network status monitoring, multilink printing

OPOS/Linux/Win8 support

Printer authentication and software bundle

High speed driver printing mode, serial port speed is 66% faster

Auto print recovering when network disconnected

Virtual serial port for USB connection

USB port supports OPOS application

100MB network interface card makes the connection and print much faster, stop receipts misprinting

## Technical Specifications

Print Method	Direct thermal printing
Emulation	ESC/POS & Line/T command sets compatible
Paper Width	80mm
Print Width	72mm
Dot Density	203dpi
Paper Roll	80mm width, 83mm diameter max.
Print Speed	300mm/sec max.
Paper Thickness	0.06~0.08mm
Interface	Serial+USB+Ethernet, or Parallel+USB
Data Buffer	128K bytes
Barcode Type	UPC-A /UPC-E /JAN13(EAN13) /JAN8(EAN8) /CODE39
	/ITF /CODEBAR /CODE93 /CODE128 /QR
	Code/PDF417
Power Supply	DC24V/2.5A
Cash Drawer	DC24V/1A
Print Head Life	150KM
Auto Cutter Life	1.5 million cuts
<b>Operating System</b>	Windows, OPOS, Linux
Net Weight	0.85kg
Dimension	139*181*127mm (W x L x H)
Warranty	2 years warranty (excluding print head)